

on street/public evcharging





Available in BLACK or WHITE – optional personalisation available

- Valid RFID card access to 3/7/22 kW rate charging
- · Charging cable locked into socket while charging
- Charging time and rate remotely configurable
- Remote management & diagnostics
- Automatic carbon footprint and management reports
- GPRS 2G network management
- Ethernet connection to host provided external internet connection
- Web access to read and download usage details, KW data and carbon footprint reports
- Future proof socket design
- Each socket has independent over and under current protection and an auto reset RCD
- Custom configuration with option for OCPP 1.5 Approved
- Renault ZE Ready configuration available
- OLEV compliant



LAR PAY As You Go

nationwide network

SPECIFICATIONS:-

Dimensions H:1400mm Diameter: 254mm Base: 340mm

Power Single phase 240V or 3 phase 400V

Sockets 2 x Type 2 (EN62196)

Communication Mode 3 module (IEC61851)

Operating Range: -20 deg C to +70 deg C

Humidity range to 90%

Status Display Blue: Available Green: In Use Red: Error

RFID standard ISO 14445/15693

Screen LCD 4x20 screen. 320x240 resolution
Warranty 1 year with optional annual extensions

RCD protection 30mA integrated

Maintenance Easy access via front door

Safety CE marked

